

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction products

Thermally toughened soda lime silicate safety glass

for use in buildings and construction works, with specification and performance as specified on page 2 in this certificate.

Product name: Pilkington Pyroclear®

placed on the market under the name or trademark of

Pilkington Deutschland AG

Haydnstraße 19

DE-45884 Gelsenkirchen, Germany

and produced in the manufacturing plant

Pilkington IGP Sp. z o.o., Przemysłowa 4, PL-96-100 Skierniewice, Poland

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard

EN 12150-2:2004

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 2019-03-29 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Issued by notified body 0402

The validity of this certificate can be verified on our website.

Martin Tillander
Product Certification Manager

Per Adolfsson
Project Manager

Certificate 0402-CPR-SC0767-18 | issue 1 | 2019-03-29

RISE Research Institutes of Sweden AB | Certification
Box 857, SE-501 15 Borås, Sweden
Phone: +46 10-516 50 00
certifiering@ri.se | www.ri.se

2017-07-06



8P07936



Specification and performance Pilkington Pyroclear®

Pilkington Pyroclear® is a thermally toughened soda lime silicate glass with thickness 6 mm, 8 mm and 10 mm.

Essential characteristic	Performance
Resistance to fire (for glass for use in a glazed assembly intended specifically for fire resistance)	E 60 E 30 E 20

For detailed information of glasses, framing system and glazing configuration, see classification reports:

C-275 38162-1, C-275 38448-1 issued by ift Rosenheim.
K-3347/597/10-MPA BS issued by iBMB MPA Braunschweig